



FASTER

TECHNICAL SHEET/SCHEDA TECNICA



DIATEX S.p.A.

Via Firenze, 4 - 36030 Villaverla (VI) Italy
info@diatex.it | www.diatex.eu



Dischi diamantati a settori per il taglio ad alta velocità di lastre ceramiche.

Segmented diamond blades for high speed cutting on Ceramic slabs.



D	W	X	Core/Anima	H
304 mm.	2,2 mm.	10 mm.	Normal	60/50
360 mm.	3,0 mm.	10 mm.	Normal & Silent	60/50
410 mm.	3,2 mm.	10 mm.	Normal & Silent	60/50

Slab Thickness	RPM Ø304	RPM Ø360	RPM Ø410	Feed speed ML/min	Feed speed 45° LM/min
6÷9 mm.	3100:3300	2800:3000	2500:2700	2,0÷2,4	1,3÷1,6
10:12 mm.	3100:3300	2800:3000	2500:2700	1,7÷2,2	1,0÷1,3
13:20 mm.	3100:3300	2800:3000	2500:2700	1,5÷2,0	0,8÷1,0

SUGGESTIONS

- IDEALE PER TAGLIO DRITTO ED INCLINATO/
SUITABLE FOR STRAIGHT AND MITER CUT
- VELOCITA' MINIMA DI TAGLIO 1,5 ML/MIN/
MINIMUM FEED SPEED 1,5 ML/MIN
- IN ENTRATA/USCITA RIDURRE VELOCITA -10%/
ENTERING/EXITING REDUCE FEED SPEED OF -10%
- ADATTO PER SPESSORI 6÷20 mm./
SUITABLE FOR 6÷20 mm. THICKNESS
- USO AD UMIDO/
WET USE
- IDEALE PER TUTTE LE SUPERFICI CERAMICHE/
SUITABLE FOR ALL CERAMIC SURFACES

